

OMB 200UNI

OMLINK

The OMB 200/300/500UNI model series are simple bargraphs designed for maximum efficiency and user comfort while maintaining their favourable price. Type OMB 200UNI is a multifunction instrument with the option of configuration for 5 various input options, easily configurable in the instrument menu.

The instrument is based on a single-chip microcontroller with an A/D converter, which secures good accuracy, stability and easy operation of the instrument.

By selecting the insertion mode of the front plexiglass (reverse/face) you may choose the required scale printing for vertical or horizontal design of the instrument.

UNIVERSAL BARGRAPH

- THREE-COLOR BARGRAPH - 20 LED
- MULTIFUNCTION INPUT (PM, OHM, RTD, DU)
- DIGITAL FILTERS, LINEARIZATION
- SIZE OF DIN 72 x 24 MM
- POWER SUPPLY 10...30 VDC/24 VAC
- Option
Comparator

OMB 200UNI

PROCESS MONITOR
OHMMETER
THERMOMETER FOR PT/NI
DISPLAY UNIT FOR LINEAR POTENTIOMETERS

OPERATION

The instrument is set and controlled by five buttons located under the front panel. All programmable settings of the instrument may be performed in two adjusting modes.

LIGHT MENU contains solely items necessary for instrument setting.

PROFI MENU contains complete instrument setting, which is accessible only via OM Link.

Standard equipment is the OM Link interface, which together with the operation program enables modification and filing of all instrument settings as well as performing firmware updates (with OML cable).

All settings are stored in the EEPROM memory (settings hold even after the instrument is switched off).

OPTION

COMPARATOR is assigned to monitor one limit value with relay output. The limit has adjustable hysteresis within full range of the display and selectable delay of the switch-on within the range of 0...99 s. Reaching the preset limits is signalled by LED and simultaneously by the switch-on of the relevant relay.

STANDARD FUNCTIONS

PROGRAMMABLE PROJECTION

Selection: of input type and measuring range

Setting: manual, in menu optional projection on the display may be set for both limit values of the input signal

Projection: 20 LED

FUNCTIONS

Linearization: through linear interpolation in 25 points (solely via OM Link)

DIGITAL FILTERS

Exponential average: from 2...100 measurements

Rounding: setting the projection step for display

EXTERNAL CONTROL

Hold: display/instrument blocking

Lock: control keys blocking

TECHNICAL DATA

INPUT

PM	Range	optional in configuration menu		
		0...20 mA	< 1,2 V	Input 1
	4...20 mA	< 1,2 V	Input 1	
	0...2 V	182 kΩ	Input 2	
	0...5 V	182 kΩ	Input 2	
OHM	Range	optional in configuration menu		
		0...100 kΩ		
RTD	Type	optional in configuration menu		
		EU > 1 000 Ω, with 3 850 ppm/°C		
NI	Type	optional in configuration menu		
		NI 1 000 with 5 000 ppm/°C	-50°...250°C	
DU	Potent. power supply	2,5 VDC/6 mA, Potentiometer resistance > 500 Ω		
External input	Connect.	1 input, on contact		
		The following functions can be assigned:		
		OFF	input off	
		HOLD	display stop	
		LOCK	control keys blocking	

PROJECTION

Display: 20 LED
Bar color: red/green/orange
Brightness: adjustable - in menu

INSTRUMENT ACCURACY

TK: 50 ppm/°C
Accuracy: ±1% of range + 1 digit
Rate: 0,5/5/50/max. measur./s
Overload capacity: 2x; 10x (t < 30 ms)
Line compensation: max. 30 Ω (RTD)
Linearization: linear interpol. in 25 points (only via OM Link)
Digital filters: exponential average, rounding
OM Link: Company communication interface for operation, setting and update of instruments.
Watch-dog: reset after 25 ms
Calibration: at 25°C and 40 % r.h.

COMPARATOR

Type: digital, menu adjustable, contact switch-on < 50 ms
Hysteresis mode: switching limit, hysteresis band „Lim ±1/2 Hys.“ and time [0...99,9 s] determining the switching delay
Output: 1x bistable with switching contact [250 VAC/30 VDC, 3 A]

POWER SUPPLY

Range: 10...30 VDC/24 VAC, ±10 %, PF ≥ 0,4, I_{STP} < 45 A/1,1 ms, isolated
Consumption: < 1,8 W/1,9 VA

MECHANIC PROPERTIES


Material: Noryl GFN2 SE1, incombustible UL 94 V-1
Dimensions: 72 x 24 x 100 mm [w x h x d]
Panel cutout: 68 x 21,5 mm [w x h]

OPERATING CONDITIONS

Connection: connector terminal blocks, section < 1,5/2,5 mm²
Stabilization period: within 15 minutes after switch-on
Working temperature: -20°...60°C
Storage temperature: -20°...85°C
Protection: IP40 [front panel only]
EL safety: EN 61010-1, A2
Dielectric strength: 2,5 kVAC per 1 min test between supply and input
Insulation resistance: for pollution degree II, measuring cat. III
 power supply > 300 V (PI)
 input, output > 300 V (PI), 150 V (DI)
EMC: EN 61326-1

PI - Primary insulation, DI - Double insulation

CONNECTION



ORDER CODE

OMB 200UNI

- -

Comparator	no	0	<input type="checkbox"/>
	1x relay (Form A)	1	<input type="checkbox"/>
Specification	customized version, do not fill in	00	<input type="checkbox"/>

Basic configuration of the instrument is indicated in bold.